

SWITCHES

oria
push button



rosa
touch button




General Specifications

- Can be configured with ETS4 / ETS5.
- Plastic push-button and metal touch-button switch series
- Wide collection option up to 6 Folds
- Product options with and without notification LED
- Optionally, icon is available.
- Different color options (see: KNX Smart home catalog)
- Easy installation to 60x60 mm standard switch junctions
- Channels are identical, each with the following functions;
 - Switching,
 - Dimming,
 - Value,
 - Scene Control,
 - Shutter/Blind Control,
 - Status notification LED

Technical Information

Protection Type	IP 20	EN 60529
Safety Class	II	EN 61140
Feed	Voltage range	21-30V DC, Over EIB/KNX data line
	Feed voltage	15 mA
	Power consumption	15 mA x 30V
Connections	EIB/KNX	Feeds through EIB/KNX data line
Operation LEDs	Programming LED for each fold	To define physical address 1 to 5 RGB LED
Button Operation Life	100.00	
Operation Temperature	Operation	-5° C + 45° C
	Storage	-25° C + 55° C
	Transportation	-25° C + 70° C
CE	Pursuant to EMC Guided and Low Voltage Regulation	

Dimensions (mm)



oria

Type	a	b	h
Single	90	9	90
1 Fold	90	9	90
2 Fold	90	9	90
3 Fold	90	9	90
4 Fold	90	9	90
5 Fold	90	9	111,5
6 Fold	90	9	133



rosa

Type	a	b	h
Single	80	8,5	80
1 Fold	80	8,5	80
2 Fold	80	8,5	80
3 Fold	80	8,5	80

